

HATHORN® DuraCAM

PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA

STANDARD CAMERAS



Industry
Leading
Warranty



Self-Leveling
Camera Heads



200 ft. to
500 ft. of
Push Rod



512Hz or 640 Hz
High Power
Sonde



For Use with
Hathorn®
Command
Modules

Hathorn® DuraCAM camera reels are designed to work with any Hathorn® control module, past, present or future. These municipal grade camera reels come fitted with your choice of Hathorn® DuraCAM self-leveling or straight view camera heads all equipped with super bright cool running LEDs for optimal picture quality. Buttwelded steel frame construction, stainless steel camera heads and your choice of cable size allow you to push further than ever before and remain in the field longer with Hathorn's legendary reliability.

Hathorn® DuraCAM camera reels are trusted by plumbers, municipalities, general contractors, home inspectors, petrochemical companies, and mining engineers to deliver a clear, recordable video inspection every time the camera is used. Designed and manufactured in North America, with a full one-year warranty.



HATHORN®
INSPECTION CAMERAS

North America 1-866-HATHORN
International 1-905-604-7040
hathorncorp.com sales@hathorncorp.com

HATHORN® DuraCAM

PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA

STANDARD CAMERAS

Specifications

Display

Size & Type Compatible with all Hathorn control modules. H12+ recommended for best picture and options.

Features

Sonde Frequency High power 512Hz or 640Hz (available only with H12+ controller)

Push Rod HPDE push rod with coax core - multiple lengths and thicknesses

Weight & Dimensions

Weight See specific item in list to the right

Dimensions (L x W x H) See specific item in list to the right

Environmental

Water Resistance - Camera & Rod IP68 to 60psi

Water Resistance - Battery Cradle IP65

Water Resistance - Reel Hub IP63

Operating Temperature 14°F to 122°F (-10°C to 50°C)

Storage Temperature -4°F to 140°F (-20°C to 60°C)



Extra Large Catalog #	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max. Pipe	Dimensions
XLR-5568/XLR-5568-SL	1.68"	Available	500 ft.	5/8"	3"	90 lbs.	12"	33" x 29" x 16"
XLR-5168/XLR-5168-SL	1.68"	Available	500 ft.	1/2"	3"	75 lbs.	12"	33" x 29" x 16"

Large Catalog #	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max. Pipe	Dimensions
LR-4168-SL / LR-4168	1.68"	Available	400 ft.	1/2"	3"	65 lbs.	12"	33" x 29" x 16"
LR-3168-SL / LR-3168	1.68"	Available	300 ft.	1/2"	3"	55 lbs.	12"	33" x 29" x 16"
LR-2168-SL / LR-2168	1.68"	Available	200 ft.	1/2"	3"	45 lbs.	12"	33" x 29" x 16"
LR-4143-SL / LR-4143	1.43"	Available	400 ft.	1/2"	3"	65 lbs.	10"	33" x 29" x 16"
LR-3143-SL / LR-3143	1.43"	Available	300 ft.	1/2"	3"	55 lbs.	10"	33" x 29" x 16"
LR-2143-SL / LR-2143	1.43"	Available	200 ft.	1/2"	3"	45 lbs.	10"	33" x 29" x 16"

Mid Catalog #	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max. Pipe	Dimensions
MR-2168-SL / MR-2168	1.68"	Available	200 ft.	1/2"	3"	42 lbs.	12"	29" x 18" x 15"
MR-2143-SL / MR-2143	1.43"	Available	200 ft.	1/2"	3"	42 lbs.	10"	29" x 18" x 15"
MR-2123-SL / MR-2123	1.23"	Available	200 ft.	.400"	2"	42 lbs.	6"	29" x 18" x 15"

Mini Catalog #	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max. Pipe	Dimensions
MN-2123-SL / MN-2123	1.23"	Available	200 ft.	3/8"	2"	33 lbs.	6"	24" x 18" x 10"
MN-2100	1"	No	200 ft.	3/8"	1.5"	33 lbs.	4"	24" x 18" x 10"

* Skids are always recommended to protect camera head. Roller skids are recommended options for pipes larger than 8". Find these accessories and spare parts on our website - www.hathorncorp.com



North America 1-866-HATHORN
International 1-905-604-7040
hathorncorp.com sales@hathorncorp.com