

HATHORN® DuraCAM

PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA

Wi-Fi CAMERAS



Industry
Leading
Warranty



Wi-Fi Reel for Use
with Phone or Tablet



Stream &
Record to
Mobile Device



Compatible with
18V Milwaukee®
or Equivalent Batteries



200 ft. to
400 ft. of
Push Rod



512Hz High
Power Sonde



6 to 8 Hours
of Runtime on
a Single Charge



Self-Leveling
Camera Heads

Hathorn® DuraCAM Wi-Fi reels stream live video directly to your mobile device. By downloading the free Hathorn app (Apple/Android) users can record video, take screen shots, and make voice commentary. Files can be shared by text, email, through the cloud or by inserting a USB key into your mobile device. Required USB dongle sold separately.

All Hathorn® DuraCAM Wi-Fi reels are compatible with 18V Milwaukee® or equivalent batteries for the ultimate in portability. Each reel is fitted with your choice of cable size and self-leveling or straight view camera heads equipped with super bright cool running LEDs for optimal picture quality.

Butt welded steel frame construction, stainless steel camera heads and Hathorn's legendary reliability allow you to remain in the field longer. Hathorn® Wi-Fi camera reels are trusted by plumbers, contractors and home inspectors, to deliver clear recordable video inspections and screen shots every time the tool is used. Designed and manufactured in North America, with a full one-year warranty.



HATHORN®
INSPECTION CAMERAS

North America 1-866-HATHORN
International 1-905-604-7040
hathorncorp.com sales@hathorncorp.com

HATHORN® DuraCAM

PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA

Wi-Fi CAMERAS



Specifications

Display

Size & Type Dependent upon Apple/Android device used

Recording, Storage & Features

Video Recording	MPEG4
Screen Shot	JPEG
File Storage	Mobile device, cloud or USB
Footage Counter	Feet or meters - resettable
Sonde Frequency	512Hz
Push Rod	HPDE - 100 to 400ft. / 1/4" to 5/8"
Start Up Time	~15 seconds

Power

Battery	Only Milwaukee® M18 18V or equivalent (not included)
Battery Life	~6-8 hrs. using 3.0Ah (sonde off)
AC/DC Adapter	12V 4.1A (included)

Environmental

Water Resistance - Camera & Rod	IP68 to 60psi
Water Resistance - Battery Cradle	IP65
Water Resistance - Reel Hub	IP63
Operating Temperature	14°F to 122°F (-10°C to 50°C)
Storage Temperature	-4°F to 140°F (-20°C to 60°C)
Wi-Fi Frequency	IEEE802.11b/g/n



Large Catalog #	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max. Pipe	Dimensions
WLR-4168-SL/WLR-4168	1.68"	Available	400 ft.	1/2"	3"	65 lbs.	12"	33" x 29" x 16"
WLR-3168-SL/WLR-3168	1.68"	Available	300 ft.	1/2"	3"	55 lbs.	12"	33" x 29" x 16"
WLR-2168-SL/WLR-2168	1.68"	Available	200 ft.	1/2"	3"	45 lbs.	12"	33" x 29" x 16"
WLR-4143-SL/WLR-4143	1.43"	Available	400 ft.	1/2"	3"	65 lbs.	10"	33" x 29" x 16"
WLR-3143-SL/WLR-3143	1.43"	Available	300 ft.	1/2"	3"	55 lbs.	10"	33" x 29" x 16"
WLR-2143-SL/WLR-2143	1.43"	Available	200 ft.	1/2"	3"	45 lbs.	10"	33" x 29" x 16"

Mid Catalog #	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max. Pipe	Dimensions
WMR-2168-SL/WMR-2168	1.68"	Available	200 ft.	1/2"	3"	42 lbs.	12"	29" x 18" x 15"
WMR-2143-SL/WMR-2143	1.43"	Available	200 ft.	1/2"	3"	42 lbs.	10"	29" x 18" x 15"
WMR-2123-SL/WMR-2123	1.23"	Available	200 ft.	.400"	2"	42 lbs.	6"	29" x 18" x 15"

Mini Catalog #	Camera Head	Self Leveling	Rod Length	Rod Size	Min. 90° Elbow	Weight	Max. Pipe	Dimensions
WMN-2123-SL/WMN-2123	1.23"	Available	200 ft.	3/8"	2"	33 lbs.	6"	24" x 18" x 10"
WMN-2100	1"	No	200 ft.	3/8"	1.5"	33 lbs.	4"	24" x 18" x 10"

* Skids are always recommended to protect camera head. Roller skids are recommended options for pipes larger than 8".
Find these accessories and spare parts on our website - www.hathorncorp.com



North America 1-866-HATHORN
International 1-905-604-7040
hathorncorp.com sales@hathorncorp.com